

DATA SHEET #SPS350

MODEL HR-2 RESIDENTIAL PENDENT SIN: AS3051

Model

 "Automatic" Residential Pendent Glass Bulb Sprinklers, Model HR-2 - 3/8" Orifice x 1/2" NPT - Pendent

K Factor

• 3.0 (4.3)

Sprinkler Identification Number (SIN)

AS3051

Approvals

UL Listed, ULC Listed

To Specify

 Furnish and install "Automatic" Sprinkler Brand Model HR-2 Residential Pendent Glass Bulb Sprinkler. Style, NPT, orifice, K-Factor, finish, and temperature rating as required.

Temperature Ratings


• 155°F (68°C)


Finishes

- Plain Brass
- Chrome Plated
- White
- Bright Brass

Note:

See back of page for ordering information and installation data.







QUICK RESPONSE SUBMITTAL SHEET

Design and Installation

The design and installation of residential sprinkler systems shall comply with the applicable standards of NFPA 13, "Installation of Sprinkler Systems in One- and Two-Family Dwellings and Mobile Homes"; NFPA 13R, "Installation of Sprinkler Systems in Residential Occupancies up to Four Stories in Height" and the Authority Having Jurisdiction.

Ordering Information

"Automatic" Model HR-2 - Residential - 3/8" Orifice x 1/2" NPT - Pendent

Туре	Temperature Rating	Maximum Ambient Temperature	K Factor	Finish	Stock Code No.	Submittal (Check One)
Model HR-2	155°F (68°C)	100°F (38°C)	3.0 (4.3)	Brass	8887320	
	(Red Bulb)			Chrome	8887321	
				White	8887327	
				Bright Brass	8887328	

Installation Data

Maximum Coverage Area (ft)		Minimum	r Flow Rate	Minimum Pressure (psi)		
		(gpm/s	Sprinkler)			
Width	Length	Single Sprinkler	Multiple Sprinkler	Single Sprinkler	Multiple Sprinkler	
12	12	9.0	9.0	9.0	9.0	
14	14	10.0	10.0	11.1	11.1	
16	16	12.0	11.5	16.0	14.7	
1	18	13.0	12.5	18.8	17.4	
20	20	16.0	14.0	28.4	21.8	

This information is only a general guideline. The company reserves the right to change any portion of this information without notice. Terms and conditions of sale apply and are available on request.

07/01 Printed in USA SPS350.QXD